



Compact Fiber Optic Distribution Frame 19" 1U

Description

Compact Fiber Optic Distribution Frame 19" 1U is a simple construction consisting of a box (with integrated front panel) and the cover. The embossments on the bottom of the ODF make it possible to organise cables and fibre-optic pigtails in an easy, functional and aesthetic way. Cable outlets are adapted for installation of cable glands M16, M20 as well as pre-terminated cables with the Fiber Quick form.



Application


Telecommunication, CATV, Monitoring, Industry, LAN, MAN, WAN.

Properties

- » Simple design,
- » Solid construction, high quality and esthetics,
- » Made of 1,0 ÷ 1,2 mm steel sheet,
- » Embossing to attach cables inside the box,
- » Four holes (two open and two closed) under the cable glands M16 and M20,
- » The cover is secured by screws,
- » Easy access to cables,
- » Standard colour: RAL7035 (light grey) glossy, RAL 9005 (black) glossy, other colours on request,
- » Dimensions [H x W x D]: 44,0x480x230 [mm],

Photos and dimensions





How to order

ODF-19-1U-C- Compact fiber optic distribution frame 19" 1U

FP12ST Front panel 19" 1U 12xST/FC/DIN d-hole
FP24ST Front panel 19" 1U 24xST/FC/DIN d-hole
FP12CS Front panel 19" 1U 12xSC/E2000 simplex *
FP24CS Front panel 19" 1U 24xSC/E2000 simplex *
FP12CD Front panel 19" 1U 12xSC/ST/FC duplex / LC quad
FP24CD Front panel 19" 1U 24xSC/ST/FC duplex / LC quad

* Suitable for LC/LX.5/MTRJ duplex SC foot print adapters

Standard equipment

» Knurled nut M5 (1 pc),

Informations

- » The ODF houses two cassettes DIN24, three cassettes DIN24 SLIM or three cassettes DIN24 WHITE,
- » Product adapted to the FiberQuick system,
- » 1U ODF 19" packed in a cardboard box.

Additional equipment

- » Cable gland M16x1,5 (cable ø5,5÷10 mm),
- » Cable gland M20x1.5 (cable ø6 ÷ ø13 mm),
- » Mounting screw M6 (4 pcs),
- » Nylon cable tie 80x2.5 mm,
- » Pigtails,
- » Splice trays,
- » Adapters.